

AttenuWave™ Perm-Rated Tape

PRODUCT DESCRIPTION

BoldStep AttenuWave Perm-Rated Tape is a heavy-duty, moisture resistant tape designed to seal seams in AttenuWave sound mat installations and to secure BoldStep Perimeter Isolation Strips to AttenuWave sound control mat fabric.

WHERE TO USE

Application

With sound mat installation.

Subfloor

All interior subfloors.

FEATURES & BENEFITS

- Tears easily
- More cost-effective than other options currently used
- Excellent bond
- Moisture resistant with a Perm rating– can be used against walls
- Watertight seal



PRODUCT INFORMATION

Perm Rating	PE35 = 0.192 US Perm Units (grains/ft²/h/inHg)
Total Thickness	7 mils (0.178 mm)
Roll Width	3 in (72 mm)
Roll Length (linear)	180 ft (54.86 m)
Tensile Strength (ASTM D-3759)	23 lbs/in
Elongation (ASTM 3759)	75%
Rolls per Box	16
Boxes per Pallet	48
Minimum Quantity	1 Box

* Physical and performance characteristics shown above are obtained from tests performed according to ASTM and PSTC test methods. BoldStep can make no warranty of any kind as to the results of the adhesive tape product use. The information published here is representative of laboratory research on these products are believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own.

INSTALLATION

Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65 °F (18 °C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65 °F (18 °C).

Note: When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.

AttenuWave Perm-Rated Tape

STORAGE AND DISPOSAL

Shelf life is one year from date of shipment when stored in a cool dry place below 76 °F (24 °C). Rolls should be stored on end. Keep in a dry, cool place. BoldStep AttenuWave Perm-Rated Tape is not considered hazardous per US-GHS requirements and may be disposed of with day-to-day construction materials.

WARRANTY AND TECH SERVICES

Contact BoldStep before your project for complete warranty information. Technical performance verification and service is available through BoldStep or BoldStep Regional Representatives throughout North America.

WARRANTY AND TECH SERVICES

See boldstep.co for complete warranty information. Technical performance verification and service is available through BoldStep or BoldStep Regional Representatives throughout North America.

JOB NAME: _____ DATE: _____

APPLICATOR: _____

BoldStep assumes no responsibility or liability for any errors or omissions in the content of this document. The information contained is subject to change without notice. Follow local and state regulations and use appropriate safety precautions and measures when installing BoldStep products. See related product literature at boldstep.co or contact BoldStep for more information prior to installation.

©2025 BoldStep. All Rights Reserved. BoldStep, ProTerra and associated logos are registered trademarks of BoldStep, Scottsdale, AZ, USA. Other trademarks, registered trademarks, product names or logos displayed are the property of their respective owners.

BoldStep
28150 N Alma School Road info@boldstep.co
Suite #103-626 (800)818-4864
Scottsdale, AZ 85262 boldstep.co

